

Solaria PowerXT[®] | AC Module



Solaria PowerXT®-355R-AC

The Solaria PowerXT AC Module combines the latest cutting-edge microinverter technology from Enphase with the premium high-efficiency and superior aestheitcs of the Solaria PowerXT Module. Utilizing the latest Enphase IQ7+ platform the PowerXT AC Module puts premium aethetics and performance together into an elegant user-friendly package that reduces installation time by combining the inverter, module and monitoring.

Achieving up to 20% efficiency, Solaria PowerXT solar modules are one of the highest power AC modules in the residential solar market. Compared to conventional modules, Solaria PowerXT modules have fewer gaps between the solar cells; this leads to higher power and superior aesthetics. Solaria PowerXT residential modules are manufactured with black backsheet and frames, giving them a striking appearance.

Higher Efficiency, Higher Power

Solaria PowerXT modules achieve up to 20% efficiency; conventional modules achieve 15% - 17% efficiency. Combined with Enphase IQ7+ microinverter the Solaria PowerXT AC Modules-is one of the highest power and most efficient AC modules available.

Easy to Install

The integrated Enphase IQ7+ microinverter reduces installation costs due to fewer balance of system components, improved two-wire cabling and is compliant with NEC 2014 & 2017 rapid shutdown requirements.

Smart Grid Ready

Meets CA Rule 21 and complies with advanced grid support, voltage and frequency ridethrough requirements. Remotely updates to respond to changing grid requirments and is configurable for varying grid profiles.

Improved Aesthetics

Compared to conventional modules the Solaria PowerXT AC Module has a more uniform appearance and superior aesthetics.

Durability and Reliability

Industry leading 25 year warranty with a million hours of microinverter testing.

About Solaria

Established in 2000, The Solaria Corporation has created one of the industry's most respected IP portfolios, with over 100 patents encompassing materials, processes, applications, products, manufacturing automation and equipment. Headquartered in Fremont, California, Solaria has developed a technology platform that unlocks the potential of solar energy allowing it to be ubiquitous and universally accessed.

The Solaria Corporation 6200 Paseo Padre Parkway, Fremont, CA 94555 P: (510) 270-2500 www.solaria.com Product specifications are subject to change without notice.



Copyright © 2018 The Solaria Corporation Rev 1B 05-23-2018



DC Input Performance at STC (1000W/m², 25° C, AM 1.5)				
Solaria PowerXT-		350R-AC	355R-AC	
Max Power (Pmax)	[W]	350	355	
Efficiency	[%]	19.4	19.6	
Open Circuit Voltage (Voc)	[V]	47.1	47.7	
Short Circuit Current (Isc)	[A]	9.49	9.56	
Max Power Voltage (Vmp)	[V]	38.8	39.5	
Max Power Current (Imp)	[A]	9.02	9.13	
AC Output Data: Enphase IQ7+ Microinverter				
Peak Output Power	[VA]	30	300	
Max Continuous Power	[VA]	290		
Nominal Voltage	[V]	24	240	
Max Continuous Current	[A}	1.	1.21	
Nominal Frequency	[Hz]	6	60	
Extended Frequency Range	[Hz]	47	47-68	
Efficiency	[%]	97	97.0	
Power Factor / Adjustable	[#]	0.7 leading.	0.7 leading0.7 lagging	
Max Branch Circuit	[A]	2	20	
Max Modules/Circuit	[#]	1	13	
Operating Temperature	[C]	-40 to +65		

Solaria PowerXT®-355R-AC

Mechanical Characteristi	cs	
Cell Type	Monocrystalline Silicon	
Dimensions (L x W x H)	1621mm x 1116mm x 40mm	
Weight	22 kg / 48 lbs	
Glass Type / Thickness	AR Coated, Tempered / 3.2mm	
Frame Type	Anodized Aluminum	
Cable Type / Length	12 AWG PV Wire (UL) / 1000mm	
Junction Box	IP67 / 4 diodes	
Front Load (UL 1703)	5400 Pa / 113 psf*	
Rear Load (UL 1703)	2400 Pa / 50 psf*	
* Refer to Solaria Installation Manual for	details	
Certifications / Warranty		
Certifications	UL 1703/UL1741/CEC	
	CAN/CSA-C22.2	
NEMA	3R	
Fire Type	Туре 1	
Power & Product Warranty	25 years*	
* Warranty details at www.solaria.com		
Packaging		
Stacking Method	Horizontal / Palletized	
Pcs / Pallet	25	
Pallet Dims	1668 x 1150 x 1230 mm	
Pallet Weight	615 kg / 1360 lbs	
Pallets / 40-ft Container	28	

[63.82±.20] 1621±5

[35.43] 900 Н

Pcs / 40-ft Container

[14.19]

[14.19] 360.50

[5.83]

[1.0] 25

[43.94±.20] 1116±5

> [1.0] 25

Disconnecting Means

Power line Enlighten Manager and MyEnlighten options Compatible with Enphase IQ Envoy Approved by UL for AC and DC load break as required by NEC Article 690 Compliant per NEC-2014 & 2017

Rapid Shutdown

Communication

Monitoring

IV Curves vs. Irradiance (350W Module)





700

[5.83] 148